


7203 BEP

Dimensions



d	17	mm
D	40	mm
B	12	mm
d ₁	≈ 26.25	mm
d ₂	≈ 21.66	mm
D ₁	≈ 31.15	mm
a	18	mm
r _{1,2}	min. 0.6	mm
r _{3,4}	min. 0.6	mm

Abutment dimensions



d _a	min. 21.2	mm
D _a	max. 35.8	mm
D _b	max. 35.8	mm
r _a	max. 0.6	mm
r _b	max. 0.6	mm

Calculation data

Basic dynamic load rating	C	10.4	kN
Basic static load rating	C	5.5	kN
Fatigue load limit	P _u	0.236	kN
Reference speed		15000	r/min
Limiting speed		20000	r/min
Calculation factor	A	0.000625	
Calculation factor	k _r	0.095	
Calculation factor	e	1.14	

Single bearing or bearing pair arranged in tandem

Calculation factor	X	0.35	
Calculation factor	Y	0.26	
Calculation factor	Y ₂	0.57	

Bearing pair arranged back-to-back or face-to-face

Calculation factor	X	0.57	
Calculation factor	Y	0.52	
Calculation factor	Y ₁	0.55	

Calculation factor

Y_2

0.93

Mass

Mass bearing

0.065

kg