

7216 BECBP

SKF Explorer

Dimensions



d	80	mm
D	140	mm
B	26	mm
d ₁	≈ 103.55	mm
d ₂	≈ 91.44	mm
D ₁	≈ 117.85	mm
a	59	mm
r _{1,2}	min. 2	mm
r _{3,4}	min. 1	mm

Abutment dimensions



d _a	min. 91	mm
D _a	max. 130	mm
D _b	max. 134	mm
r _a	max. 2	mm
r _b	max. 1	mm

Calculation data

Basic dynamic load rating	C	85	kN
Basic static load rating	C	75	kN
Fatigue load limit	P _u	3.05	kN
Reference speed		4000	r/min
Limiting speed		5600	r/min
Calculation factor	A	0.0801	
Calculation factor	k _r	0.095	
Calculation factor	e	1.14	

Single bearing or bearing pair arranged in tandem

Calculation factor	X	0.35
Calculation factor	Y	0.26
Calculation factor	Y ₂	0.57

Bearing pair arranged back-to-back or face-to-face

Calculation factor	X	0.57
Calculation factor	Y	0.52

Calculation factor	Y_1	0.55
Calculation factor	Y_2	0.93

Mass

Mass bearing		1.45	kg
--------------	--	------	----