



# NKXR 35 Z

## Dimensions



F <sub>w</sub>	35	mm
D	47	mm
C	30	mm
C <sub>1</sub>	12	mm
C <sub>2</sub>	9	mm
d	35	mm
D <sub>2</sub>	53.2	mm
r <sub>1,2</sub>	min. 0.6	mm

## Abutment dimensions



d <sub>a</sub>	min. 47.7	mm
r <sub>a</sub>	max. 0.6	mm
r <sub>b</sub>	max. 0.3	mm
d <sub>i</sub>	30	mm
F	35	mm
B <sub>i</sub>	20	mm

## Calculation data

Basic dynamic load rating, radial direction	C	24.6	kN
Basic static load rating, radial direction	C	45	kN
Basic dynamic load rating, axial direction	C	29	kN
Basic static load rating, axial direction	C	93	kN
Fatigue load limit, radial direction	P <sub>u</sub>	5.6	kN
Fatigue load limit, axial direction	P <sub>u</sub>	9.15	kN
Minimum axial load factor	A	0.000692	
Reference speed		2800	r/min
Limiting speed		5600	r/min

## Mass

Mass bearing	0.17	kg
--------------	------	----

## Associated products

Inner ring	IR 30x35x20
------------	-------------

